

HEAVY-DUTY **CONSTRUCTION FORKS**

FOR HEAVY LIFTING APPLICATIONS





- Perfect for demanding applications such as oil field work and heavy lifting
- Breakout force rated tines
- · Heavy-duty tine shaft and fully welded tine bosses deliver years of dependable performance
- Tines always stay close to the frame, even when dumping, preventing operator error and improving safety
- Simple and fast tine adjustment means more loading and less struggling with hard to move tines
- Many tine lengths and frame widths available to suit any application

Specifications*					
Straight Tip Load (Lbs.)	0-16,700	16,700-27,000	27,000-42,500	42,500-64,000	64,000-79,000
Tine Size (")	2.5" Thick x 6" Width	3" Thick x 7" Width	3.5" Thick x 8" Width	4" Thick x 8" Width	4.5" Thick x 12" Width
Tine Load Rating at 24" Center (Lbs.)	21,150	33,000	53,000	67,000	122,300
Backframe Height (")	45.5	48.5	55	56	62.5
Tine Lengths (")	48, 60, 72, 84, 96	60, 72, 84, 96	60, 72, 84, 96	60, 72, 84, 96	60, 72, 84, 96
Backframe Width (")	60, 72, 84, 96, 102 ,106	60, 72, 84, 96, 102, 106	72, 84, 96, 102, 106	72, 84, 96, 102, 106	72, 84, 96, 102, 106

Proudly Made in USA

*Specifications subject to change without notice.

WARRANTY Rockland Heavy-Duty Construction Forks are guaranteed against failure due to defective design, materials, or workmanship for a period of two years or 4,000 hours.

WWW.ROCKLANDMFG.COM | SALES@ROCKLANDMFG.COM | 1-800-458-3773