



CG CANE GRAPPLE

CUT CANE HANDLING COSTS

Rockland CG Cane Grapples mounted on a wheel loader are the modern, low-cost solution to cane handling problems. Reduce cane handling costs dramatically by eliminating ground labor and revolving cranes. Capitalize on the speed and maneuverability of a wheel loader. Productivity is increased while payroll and equipment expenses are reduced by mounting a Rockland CG Cane Grapple on your wheel loader.



CG Cane Grapples are built to handle cane season after season without costly down time or aggravating repairs. They are built of high-strength, weight-saving, alloy steels to keep grapple weight to a minimum while delivering maximum payloads. Heavy-duty hydraulics, oversized clamp bearings and reinforcement at all critical stress areas underscore typical Rockland dedication to design excellence—a dedication that pays off on the job. Rockland CG Cane Grapples are available in capacities designed to match the lift and carry capacity of the loader upon which it will be mounted. Rockland CG Cane Grapples have proven themselves at cane mills around the world.

SPECIFICATIONS

Machine Category	20		30,40		50,60	
Model	CG-6		CG-8		CG-10	
	with kicker	w/o kicker	with kicker	w/o kicker	with kicker	w/o kicker
Backframe Height (")	42 <small>1067</small>	42 <small>1067</small>	57 <small>1448</small>	57 <small>1448</small>	57 <small>1448</small>	57 <small>1448</small>
Tine Clearing Spacing (")	23 <small>584</small>	23 <small>584</small>	16 <small>406</small>	16 <small>406</small>	23 <small>584</small>	23 <small>584</small>
Overall Width (")	80 <small>2032</small>	80 <small>2032</small>	96 <small>2438</small>	96 <small>2438</small>	128 <small>3271</small>	128 <small>3271</small>
Kicker Width (")	36 <small>914</small>	N/A	50 <small>1270</small>	N/A	68 <small>1727</small>	N/A
Tine Length (")	54 <small>1372</small>	54 <small>1372</small>	66 <small>1676</small>	66 <small>1676</small>	72 <small>1829</small>	72 <small>1829</small>
Clamp Width (")	50 <small>1270</small>	50 <small>1270</small>	59 <small>1499</small>	59 <small>1499</small>	94 <small>2387</small>	94 <small>2387</small>
Number of Tines	4	4	6	6	6	6
Weight (lbs.)	3900 <small>1769</small>	3100 <small>1406</small>	5400 <small>2449</small>	4200 <small>1905</small>	7200 <small>3266</small>	6900 <small>3130</small>

(mm/kg)

Specifications subject to change without notice.

INSTALLATION INFORMATION

All CG Cane Grapples come complete with jumper hoses ready to mount in place of the standard bucket using factory pins or specified coupler brackets. A three-spool valve and boom arm piping are required to complete the installation.

WARRANTY

Rockland Cane Grapples are guaranteed against failure due to defective design, materials or workmanship for a period of two years or 4000 hours.



Distributed by:

ROCKLAND MANUFACTURING CO.
 P O BOX 5
 800-458-3773
 BEDFORD, PA 15522
 www.rocklandmfg.com