

HKR-T TILTING COUPLER

Tilt your attachment instead of rotating your machine!

The safety, simplicity, and reliability of the HKR coupler has been combined with the XtraTilt Power Actuator that will transform the productivity of your excavator.

With a tilt angle of 180 degrees on all models, this groundbreaking product will increase the versatility of your attachments in multiple applications. The HKR-T coupler allows you to expand the working envelope of your machine and eliminates the need to level your tracks when doing fine grading work.






Key Features

- HKR-T Coupler includes all HKR safety features
- Simple & robust design
- Tilt angle of 180 degrees
- Single cylinder operation, removing complexity
- XtraTilt Power Actuator- essentially maintenance and wear-free
- Exceeds global safety standards
- Available for excavators 3T-20T

ROBUST & SIMPLE DESIGN

The HKR-T has been proven to be the most reliable tilting quick coupler on the market today. The XtraTilt Power Actuator is self-lubricating and essentially maintenance free, so that you are able to concentrate on more important tasks. No exposed tilt cylinders mean never having to worry about damage or failure of critical components.

XtraTilt Power Actuator



Specifications*

MACHINE WEIGHT (LBS)	PIN CENTER RANGE INCHES (MM)	BOTTOM FRAME WIDTH INCHES (MM)	MAX TILT ANGLE (DEGREES)
0-5,000	6.38-8.54 (162-217)	4.61 (117)	180°
5,001-15,000	8.50-10.71 (216-272)	5.71 (145)	180°
15,001-25,000	10.98-14.02 (279-356)	6.5 (165)	180°
25,001-33,000	13.58-17.13 (345-435)	8.66 (220)	180°
33,001-40,000	15.20-20.08 (386-510)	11 (279)	180°
40,001-52,000	15.20-20.08 (386-510)	11.81 (300)	180°

Proudly Made in USA

*Specifications subject to change without notice.

HKR-T Tilting Coupler In Action









WARRANTY Rockland Excavator Tilt Couplers are guaranteed against failure due to defective design, materials, or workmanship for a period of two years or 4,000 hours.