



EX EXCAVATOR RAKES

**CLEAR LAND EFFICIENTLY
WITH AN EXCAVATOR**

Turn your excavator into an efficient land clearing machine with a Rockland Excavator Rake. The rake's long, tough, teeth are built of high-strength heat-treated alloy steel for years of heavy-duty land clearing service. They are curved for maximum rolling and sifting action. They project forward far enough so that loading land clearing debris is fast and efficient. If the job requires handling large capacity loads, use the EX Excavator Rake with a Rockland thumb to obtain maximum material handling capability.



EXCAVATOR RAKE SPECIFICATIONS

Machine Class	AA	A	B	C	D	E
Excavator Weight (lbs.)	15,001 to 25,000 4538 to 11343	25,001 to 33,000 11343 to 14973	33,001 to 52,000 14973 to 23593	52,001 to 70,000 23594 to 31760	70,001 to 90,000 31761 to 40835	90,001 to 110,000 40835 to 49909
Raking Width (")	44 <i>1118</i>	48 <i>1219</i>	51 <i>1295</i>	55 <i>1397</i>	56 <i>1422</i>	79 <i>2007</i>
Clear Spacing (")	13 <i>330</i>	14 <i>356</i>	15 <i>381</i>	16 <i>406</i>	16 <i>406</i>	23 <i>584</i>
Number of Teeth	4	4	4	4	4	4
Tooth Penetration (")	12 <i>305</i>	16 <i>406</i>	16 <i>406</i>	20 <i>508</i>	20 <i>508</i>	20 <i>508</i>
Tooth Thickness (")	1.25 <i>32</i>	1.5 <i>38</i>	1.5 <i>38</i>	1.75 <i>44</i>	2 <i>51</i>	2.5 <i>64</i>
Weight (lbs.)	610 <i>277</i>	1180 <i>535</i>	1400 <i>635</i>	1810 <i>821</i>	2145 <i>973</i>	3470 <i>1574</i>

(mm/kg)

Specifications are subject to change without notice.

INSTALLATION INFORMATION

All Rockland Excavator Rakes mount in place of the existing bucket using factory pins.

WARRANTY

Rockland Excavator Rakes are guaranteed against failure due to defective design, workmanship or materials for a period of two years or 4000 hours.



Distributed by:

ROCKLAND MANUFACTURING CO.
P O BOX 5
800-458-3773

BEDFORD, PA 15522
www.rocklandmfg.com