



YM LOG GRAPPLES

WEST COAST STYLE

YM FOR LARGE DIAMETER LOADS

The YM grapple has maximum capacity for large diameter loads. Rockland YM's have been used for unloading trucks of tree length logs on the East Coast and for handling redwood on the West Coast. Rockland YM grapples are at work in Africa, Asia, and South America. They have proven themselves under the toughest applications on the largest wheel loaders. The rugged, independent clamps grip the load over each tine for maximum stability. Grapple shape guarantees easy log rollup and full loads every pass. If you have to handle large loads with a large machine, specify the Rockland YM for years of dependable service.



SPECIFICATIONS

Category	40	50	60	70	80	90
Overall Width (")	94 <small>2388</small>	94 <small>2388</small>	110 <small>2794</small>	110 <small>2794</small>	112 <small>2845</small>	112 <small>2845</small>
Tine Width (")	7 <small>178</small>	8 <small>203</small>	10 <small>254</small>	12 <small>305</small>	12 <small>305</small>	12 <small>305</small>
Min. Clamp Opening (")	46 <small>1168</small>	50 <small>1270</small>	65 <small>1651</small>	65 <small>1651</small>	70 <small>1778</small>	75 <small>1905</small>
Height to Clamp Pivot (")	60 <small>1524</small>	60 <small>1524</small>	72 <small>1829</small>	90 <small>2286</small>	110 <small>2794</small>	120 <small>3048</small>
Max. Clamp Opening (")	101 <small>2565</small>	118 <small>2997</small>	125 <small>3175</small>	135 <small>3429</small>	145 <small>3683</small>	155 <small>3937</small>
Tine Length to Backframe (")	54 <small>1372</small>	60 <small>1524</small>	72 <small>1829</small>	84 <small>2134</small>	96 <small>2438</small>	96 <small>2438</small>
Weight (lbs.)	3500 <small>1589</small>	4500 <small>2043</small>	5500 <small>2497</small>	8200 <small>3723</small>	10000 <small>4540</small>	11200 <small>5085</small>

(mm/kg)

Specifications subject to change without notice.

MOUNTING INFORMATION

All Rockland grapples mount in place of the standard bucket using factory pins or specified coupler brackets. Grapples are equipped with all necessary piping and hydraulics including jumper hoses which connect to the loader boom arm piping. A 3-spool valve and boom arm piping are required on the loader to complete the installation.

WARRANTY

Rockland YM Log Grapples are guaranteed against failure due to defective design, materials or workmanship for a period of two years or 4000 hours.



Distributed by:

ROCKLAND MANUFACTURING CO.
P O BOX 5 **BEDFORD, PA 15522**
800-458-3773 **www.rocklandmfg.com**